

XP 002153967

AN - 1986-004915 [25]
AP - JP19840090802 19840504
CPY - DAIM-N
DC - G03 P85
FS - CPI;GMPI
IC - C09J7/02 ; G09F3/02
MC - G03-B04
PA - (DAIM-N) DAIMATSU KAGAKU KOGYO KK
PN - JP60233178 A 19851119 DW198601 007pp
PR - JP19840090802 19840504
XA - C1986-002351
XIC - C09J-007/02 ; G09F-003/02
XP - N1986-003465
AB - J60233178 Material comprises (a) a surface substrate; (b) a first pressure sensitive adhesive layer (II) laminated to the face of (a); (c) a second pressure sensitive adhesive layer (III) laminated to (b); and (d) a release sheet tentatively adhered to (c).
- USE/ADVANTAGE - Used as label or sticker which is applied using the laminated adhesives. Since pressure sensitive adhesive layers have different properties and are laminated consecutively, the initial bond strength is retained sufficiently, and once it is adhered, it exhibits good adhesion durability with no squeeze out of adhesives. (II) contains pre-sure sensitive adhesive with relatively inferior adhesion but superior adhesion durability. (III) contains a pressure sensitive adhesive with relatively superior low temp. adhesion.
IW - ADHESIVE LABEL STICKER COMPRISE SUBSTRATE TWO PRESSURE SENSITIVE ADHESIVE LAYER RELEASE SHEET
IKW - ADHESIVE LABEL STICKER COMPRISE SUBSTRATE TWO PRESSURE SENSITIVE ADHESIVE LAYER RELEASE SHEET
NC - 001
OPD - 1984-05-04
ORD - 1985-11-19
PAW - (DAIM-N) DAIMATSU KAGAKU KOGYO KK
TI - Adhesive label or sticker - comprising substrate, two pressure sensitive adhesive layers and release sheet